

TECHNICAL DATA SHEET

LED Down Light / EN-DLE015 series

VERSION - 25.07.2017

STANDARD LUMINAIRE

Reference	EN-DLA015
Power	15 W
Current	350 mA
Protection Class	IP20
Voltage	AC220-240V, 50-60Hz
Led Type	Cree Cob
CRI	80+
Beam Angle	20°, 40°, 60°
Dimmable	Yes optionnal
Working T°	-20°C ~ +45°C
Warranty	5 years

COLOR TEMPERATURE & LUMINOUS FLUX

EN-DLI015 series

2'700K	3'000K	4'000K	5'000K
1125 lm ±5%	1200 lm ±5%	1290 lm ±5%	1350 lm ±5%

FINISH

Standard	White OR Silver
----------	-----------------

ON REQUEST

Beam Angle	20°, 40°, 60°
Protection Class	IIP44 for compact structure
Dimming Option	Triac <i>Ask technical departement for more information</i>



APPLICATION:

- perfect replacement for halogen lamp, incandescent bulb
- recessed lighting
- comemrcial lighting
- IP44 option for compact structure,

MAIN FEATURES:


- beam direction adjustable with titable structure
- unique designed reflector for a perfect light distribution
- different fixtures & cut-outs selectable
- IP44 option for compact structure,

CERTIFICAT




TECHNICAL DRAWINGS & DIMENSIONS - EN-DLE015 series

EN-DLE015-R80




Cut-out: ø70mm

EN-DLE015-R90




Cut-out: ø75mm

EN-DLE015-R110




Cut-out: ø90-100mm

EN-DLE015-S80




Cut-out: 70x70mm

EN-DLE015-S90



Cut-out: 75x75mm

EN-DLE015-S110



Cut-out: 90-100x90-100mm



TECHNICAL DATA SHEET

LED Down Light / EN-DLE015 series

VERSION - 25.07.2017

TECHNICAL DRAWINGS & DIMENSIONS - EN-DLE015 series

	<p>EN-DLE015-R70</p>  <p>Cut-out: ø60mm</p>		<p>EN-DLE015-R70-1</p>  <p>Cut-out: ø60mm</p>
	<p>EN-DLE015-R80-2</p>  <p>Cut-out: ø70mm</p>		<p>EN-DLE015-R88-2</p>  <p>Cut-out: ø75-80mm</p>
	<p>EN-DLE015-R82-3</p>  <p>Cut-out: ø70mm</p>		<p>EN-DLE015-R88-3</p>  <p>Cut-out: ø75-80mm</p>
	<p>EN-DLE015-R70-4</p>  <p>Cut-out: ø60mm</p>		<p>EN-DLE015-R90-4</p> <p>IP44</p>  <p>Cut-out: ø70mm</p>